

www.unibatitalia.com 

Unibat

DUAL AGM

MAINTENANCE FREE DEEPCYCLE BATTERY

Marine & Leisure



Le batterie Unibat DUAL AGM forniscono ad imbarcazioni, e camper un elevato livello di affidabilità per le numerose utenze elettriche. Progettate per l'utilizzo sia in avviamento che per l'alimentazione degli impianti sono le uniche batterie in grado di garantire il corretto e continuo funzionamento di impianti con un elevato fabbisogno energetico, quali ad esempio il sistema di refrigerazione/riscaldamento a veicolo fermo, radar, sonar, prevenendo l'usura precoce della batteria e i conseguenti tempi di fermo. Non necessitano di manutenzione.

The maintenance-free Unibat DUAL AGM batteries provide heavy commercial vehicles and campers with a high level of reliability for their numerous electronic consumers. Designed for use both in start-up and for powering the systems, they are the only batteries capable of guaranteeing the correct and continuous operation of systems with a high energy requirement, such as for example the refrigeration / heating, radar, sonar, system with the vehicle stationary, preventing premature battery wear and consequent downtime.

Leisure Battery Applications

Special Design per applicazioni a lunga durata

Special Design for Deep Cycle Applications

Avviamento motore	Argano elettrico	Illuminazione		Elica di prua	
<i>Starter Motor</i>	<i>Electrical winches</i>	<i>Lighting</i>		<i>Bow thruster</i>	
Pilota Automatico	Scalda acqua	Frigorifero / congelatore		Forno e microonde	
<i>Autopilot</i>	<i>Water heater</i>	<i>Refrigerator / icebox</i>		<i>Microwave and electric oven</i>	
Ecoscandaglio	Condizionatore	Luci di ingombro		Lavastoviglia	
<i>Fish finder</i>	<i>Air conditioner</i>	<i>Position lights</i>		<i>Dishwasher</i>	
Radar	Sat/TV	Radio SSB		Pumps	

more information at www.unibatitalia.com



Marine & Leisure

	CB200M	CB260M
Constant voltage (V)	12V	12V
Constant capacity (20hr/10.5v)	200Ah @25°C (77°F)	260Ah @25°C (77°F)
Dimension	L 506 x W 240 x H 246 mm	L 515 x W 262 x H 246 mm
Weight	~ 54 Kg (120.15 lbs)	~ 62 Kg (136.68 lbs)
CCA @25°C (77°F)	1230A	1500A
Idle capacity (25A, 10.5V)	450 min	560 min
Operation temperature	~ 20°C ~ 60°C	~ 20°C ~ 60°C
Acceptable charging current	0 ~ 60A	0 ~ 78A
Recycle charging current	14.5V ~ 15.0V	14.5V ~ 15.0V
Self-discharge @25°C (77°F)	< 8% (store for 90 days)	< 8% (store for 90 days)
Case materials	High temp. resistant pp material	High temp. resistant pp material
Typor of terminal	Tapered terminal (Left:-; Right:+)	Tapered terminal (Left:-; Right:+)

